

Maco C-TS

Multi-point security locking system

For use on PVCu, timber or composite doors with a 16mm Eurogroove

MACO Protect C-TS is a highly secure combined lift lever and split spindle door lock. It enables the fabrication of a wide range of easy to operate door styles from an individual highly secure door lock. The spindle type controls the function of the lock, solid spindle bar for lift lever function and split spindle pack for split spindle function.



Features and Benefits

- 35mm and 45mm backsets available
- Single door lock for use as a lift lever or split spindle operated door lock (split spindles sold separately)
- Smaller compact lockcases
- Single and double door configurations available - including double door mullion free version
- Dead bolt operated from lever handle reducing force required to lock door
- Non-handed lock design
- Suitable for sprung and unsprung handle sets
- Forged steel dead bolt locking hooks for increased security
- High levels of adjustability through adjustable striker plates and locking cams
- Faceplate lengths available 2200mm for single doors, 1800mm for double doors and 1500mm slave door lock
- Endurance tested to 50,000 operations
- PAS24-2012 capability
- MACO silver look surface treatment tested to 480 hours Class 5 EN 1670 corrosion resistance
- Available in MACO TriCOAT Plus surface technology - phone for details
- 16mm and 20mm faceplate available (3mm thick)
- Locking options: 2 hook, 2 hook-cam and 2 hook-cam + 2 cam
- Standard 1050mm handle height
- 92mm handle to cylinder centres
- 8mm square shaft

Details

Cam

Adjustable cam for compression

Hook

For optimum security

Striker plates

Profile specific
Produced from high quality zinc and steel
Adjustable individual or single piece
Available for both 1800mm and 2200mm locks
Contact Technical for codes

Manufactured from

Produced from high quality zinc and steel

Recommended screws

No.8 countersunk or equivalent.
For TriCOAT finish ensure TriCOAT screws are used

Standards

PAS 24 and BS6375 Parts 1 & 2
BS EN 1670

Finishes

Silver chromate
TriCOAT (high corrosion resistance) also available

More information

enquiries@titon.co.uk / 01206 713801

Example Door Lock Configurations

